




Presentation Part Number: WM 222.301

Extended Height Adjustable Arm, Vertical Din rail mounting. Supported weight balancing range from 4 to 9 Kg. Overhead mount





# Extended Height Adjustable Arm, Vertical Din rail mounting. Supported weight balancing range from 4 to 9 Kg. Overhead mount

When the only available mounting point is high up, this arm gains those crucial extra centimeters lower for ergonomic ease. The Arm extends far in to working space, height adjustes and can be folded back neatly when not use. You need extended reach for your monitor? And the only available mounting position is too high to reach your device? This arm was especially designed for high mounting positions. The arm steps down from the first and second joint. Cable integration offers a neat and clean working environment. A medical-grade arm with easy-to-clean and infection control friendly surfaces, a 5-year warranty and a 6-fold safety factor.

#### **Technical specifications:**

- \* Integrated cable passage \* Equipotential bonding
- \* Fixing on the chosen adapter solution
- \* This Horizontal extended Arm with gas spring simply adjusts to the desired height and is fixed. \* It has a safety stop button for height adjustment, which allows the arm to remain in the chosen position. \* The head of this arm complies with the VESA 75/100 mm screen mounting standard.
- \* Compatible with screens weighing no more than 4-9 Kg. \* Stability touch screen.
- \* Screen tilt: 30° down and 90° up. Screen rotation: 130° right, 180° left.
- \* Arm rotation: 90° right, 90° left. \* Height adjustment: 45° down, 45° up
- \* Total length 808 mm
- \* All our medical arms are CE, ROHS, Medical Grade, Regulations MDD 93/42 ECC compliant.
- \* Colour RAL 5013 cobalt blue and RAL 9016 traffic white
- \* Warranty: 5 years











## **Technical Specifications**

Extended Height Adjustable Arm, Vertical Din rail mounting. Supported weight balancing range from 4 to 9 Kg. Overhead mount










Monitor adaptation: VESA 75/100 mm Colour: Decorative parts: RAL 5013 cobalt blue Aluminium parts: RAL 9016 traffic white Max. load capacity of the support arm: 22 kg Max. load capacity of the monitor: 18 Kg Monitor adaptation max. load: 18 Kg

Balancing scale for this medical arm: 4 - 9 Kg

Product weight: 5,2 Kg

**Height adjustment:** Parallel mechanism for a constant viewing angle Safety: Has a safety stop button for the height adjustment, which allows the medical arm to remain in the chosen position.













**Mounting Information - Din Rail Horizontal** 

Extended Height Adjustable Arm, Vertical Din rail mounting. Supported weight balancing range from 4 to 9 Kg. Overhead mount

#### Din Rail Vertical:

Fixed standard rail clamp For mounting on horizontal standard rail 10 x 25 mm













## **Mounting information - Mounting options**

Extended Height Adjustable Arm, Vertical Din rail mounting. Supported weight balancing range from 4 to 9 Kg. Overhead mount

#### Where do you want to mount the support arm?

At the hospital, there are different ways to fix our brackets: round tube, standard rail, wall rail or on an anaesthesia machine. We will always provide you with the adapter you need.



Adapter for vertical wall slide
For wall slide mounting



Adapter for Amico remote controls and wall panels



Adapter for Mindray medical power supply units



Double clamp for vertical standard rail For mounting on two parallel vertical standard

rails 10 x 25 mm



rail
For mounting on a horizontal standard rail 10 x 25, 8 x 35, 10 x 30, 10 x 50 mm

Fixed clamp for a standard



**tube**For mounting on round tube ø 25, 35, 38 mm

Fixed clamp for round



Adapter for Maquet anaesthesia machines Cone Adapter for Model FLOW i



Adapter for Löwenstein anaesthesia machines Medical Adapter for Leon / Leon plus



Universal round tube clamp V-clamp for mounting on round tube ø 23 - 40 mm







## **Mounting information - Mounting options**

Extended Height Adjustable Arm, Vertical Din rail mounting. Supported weight balancing range from 4 to 9 Kg. Overhead mount

#### Where do you want to mount the support arm?

At the hospital, there are different ways to fix our brackets: round tube, standard rail, wall rail or on an anesthesia machine. We will always provide you with the adapter you need.



Adapter for anesthesia machine (all suppliers) H 80 mm, with existing side rail



Clamp for a vertical standard rail For mounting on standard rail 10 x 25 mm



Considered to be the world's best in advanced hygiene control, our medical mounting systems include cable integration, a 5-year maintenance-free warranty and medical grade compliance. We're simply the best in the world at what we do.







## Compatible accessories for this mount

Extended Height Adjustable Arm, Vertical Din rail mounting. Supported weight balancing range from 4 to 9 Kg. Overhead mount

#### Compatible accessories for this Medical Arm

You can complete your installation with these additional accessories:



**Triple hook for cable**For mounting on support arm



**Double hook for cable**For mounting on support
arm



Downward pole with cable hook
For mounting on support arm



Double handle with VESA mounting
For VESA monitors



Handle for VESA monitor support For VESA monitors



**Double hook for cable**For wall or column rail
mounting



**Triple hook for cable**For wall or column rail mounting



**Basket**For wall or column rail mounting



**Downward Pole**For mounting on support arm

