



### Presentation

### Part Number: WM 225.219

Medical Combo arm Standard adjustable in height by 2 x 300 mm, Mounting on Anesthesia Machines (All manufacturers). Supported weight balancing range from 13 to 16 Kg



pliers) fournisseurs) nte ranciers)		
Adapter for anaesthesia machines (all suppliers) H 80 mm, with existing side channel Adaptateur pour machine d'anesthesia (tous les fournisseurs) H 80 mm, avec glissière latérale existante Adapter voor anesthesiaepparatuur (alle leveranciers) H 80 mm, met bestaande zijkanaal	0 0	
sthesia macl vith existing he d'anesthé c glissière la lesieapparat net bestaan		
H 80 mm, v H 80 mm, v pour machir 80 mm, ave voor anesth H 80 mm,		
Adaptateur H Adaptateur		

This 2 x 300 mm long height adjustable Combo Medical Arm allows to fix, orientate and adjust perfectly a screen, its keyboard support with dimensions of 500 x 202 mm delivered with this configuration allows to welcome a standard keyboard as well as a mouse. As an option, it can be equipped with a stand with a sliding right/left mouse tray with dimensions of 480 x 220 mm for the keyboard and 226 x 220 mm for the mouse, or with a large keyboard stand with dimensions of 580 x 200 mm. It has a safety stop button for the height adjustment, which allows the arm to remain in the selected position.

Technical specifications:

\* Integrated cable channel \* Standard keyboard support of 500 x 202 mm

\* This standard Combo Arm with height adjustment of 2 x 300 mm in length simply attaches to the existing rail of the anaesthesia machine and then adjusts to the rail with the universal adapter and clamps with the two grips.

\* The head of this arm conforms to the VESA 75/100 mm screen mounting standard

\* Compatible with equipment weighing up to 13 - 16 Kg.

\* Screen tilt: 10° \* Arm rotation: 90° to the right, 90° to the left from the mounting point \* Keyboard and screen support rotation: 100° to the right, 100° to the left.

- \* Rotation of the central axis between the two arms 180°.
- \* Total length of the configuration 1087 mm

\* Colour RAL 5013 cobalt blue and RAL 9016 traffic white \* Warranty: 5 years









## **Technical specifications**


Part Number: WM 225.219

Medical Combo arm Standard adjustable in height by 2 x 300 mm, Mounting on Anesthesia Machines (All manufacturers). Supported weight balancing range from 11 to 14 Kg









Monitor adaptation: VESA 75/100 mm Color: Decorative parts: RAL 5013 cobalt blue Aluminium parts: RAL 9016 traffic white Balance scale of this medical arm: 13 - 16 Kg Product weight: 6,4 - 7,9 Kg (depending on the dimensions of the keyboard tray) Height adjustment: Parallel mechanism for a constant viewing angle

**Safety:** Has a safety stop button for height adjustment, which allows the medical arm to remain in the chosen position.













Mounting Information - Adapter Anesthesia Machines

Part Number: WM 225.219

Medical Combo arm Standard adjustable in height by 2 x 300 mm, Mounting on Anesthesia Machines (All manufacturers). Supported weight balancing range from 11 to 14 Kg

Mounting with adapter on anaesthesia rail:

Mounting on existing anaesthesia machine rail (all manufacturers) Adapter Included in this configuration







#### **Product highlights:**

The height adjustable arms offer full cable integration and easy cleaning for infection control in all critical care areas of the clinical environment. Our 5-year warranty ensures reliable, trouble-free and maintenance-free operation. The swivel function at the point of attachment as well as the tilt and swivel function of the monitor adaptation offer optimal positioning of your device. The height-adjustable arm in its extended version is a two-part arm with a central pivot point between the two arm sections. All bottom mounted monitors have the safety feature of a 20° tilt stop.







# **Mounting Information - Mounting Options**

Part Number: WM 225.219

Medical Combo arm Standard adjustable in height by 2 x 300 mm, Mounting on Anesthesia Machines (All manufacturers). Supported weight balancing range from 11 to 14 Kg

### Where do you want to mount the support arm?

At the hospital, there are different ways to fix our brackets: round tube, standard rail, wall rail or on an anaesthesia machine. We will always provide you with the adapter you need.



Adapter for vertical wall slide For wall slide mounting



Double clamp for vertical standard rail For mounting on two parallel vertical standard rails 10 x 25 mm



Adapter for Maquet anaesthesia machines Cone Adapter for Model FLOW i



Adapter for Amico remote controls and wall panels



Fixed clamp for a standard rail For mounting on a horizontal standard rail 10 x 25, 8 x 35, 10 x 30, 10 x 50 mm



Adapter for Löwenstein anaesthesia machines Medical Adapter for Leon / Leon plus



Adapter for Mindray medical power supply units



Fixed clamp for round tube For mounting on round tube ø 25, 35, 38 mm



Universal round tube clamp V-clamp for mounting on round tube ø 23 - 40 mm







## **Mounting Information - Mounting Options**

Part Number: WM 225.219

Medical Combo arm Standard adjustable in height by 2 x 300 mm, Mounting on Anesthesia Machines (All manufacturers). Supported weight balancing range from 11 to 14 Kg

#### Where do you want to mount the support arm?

At the hospital, there are different ways to fix our brackets: round tube, standard rail, wall rail or on an anaesthesia machine. We will always provide you with the adapter you need.



Adapter for anaesthesia machine (all suppliers) H 80 mm, with existing side rail



**Clamp for a vertical standard rail** For mounting on standard rail 10 x 25 mm





Considered to be the world's best in advanced hygiene control, our medical mounting systems include cable integration, a 5-year maintenance-free warranty and medical grade compliance. We're simply the best in the world at what we do.







Technical drawing of this Combo configuration

Part Number: WM 225.219

Medical Combo arm Standard adjustable in height by 2 x 300 mm, Mounting on Anesthesia Machines (All manufacturers). Supported weight balancing range from 11 to 14 Kg

